



Fanvil



Fanvil i16S-02P/i16SV-02P SIP Intercom

Fanvil i16S-02P/i16SV-02P SIP Intercom is designed for outdoor scenes with high reliability, HD Audio/Video, and IP65/IK10 protection grade. It combines security, audio/video intercom and broadcasting functionalities and offer the best communication solution for users.

Highlights

- ✔ Built-in HD camera with infrared night vision, adopt H.264 codec (only i16SV-02P)
- ✔ IP65 waterproof and dustproof.
- ✔ IK10 anti-collision with robust die-cast aluminum frame
- ✔ Anti-tamper- alarming as long as the cover is apart from the housing, and reporting to the control center at the same time
- ✔ HD voice speech quality with built-in 3W speaker and Acoustic Echo Cancellor
- ✔ Audio line out port, expandable external active speaker.
- ✔ Built-in 2 short-in detect port and 2 short-out control port
- ✔ Support built-in TF card slot for data storage or audio offline broadcasting.



i16S-02P



i16SV-02P

Model	Network	Button	Camera
i16S-02P	10/100Mbps	2	×
i16SV-02P	10/100Mbps	2	✓



Generic

- 2 SIP lines
- Speed dial
- Linkage with IP camera to realize video intercom
- Oral announcement of the IP address(in English)
- MP3 broadcasting
- Support programmable DSS key
- Support mono active speaker
- Talkback recording output
- Switch signal input and output
- Support TF card
- PoE enabled

Device Functions

- Auto-answering
- Programmable DSS keys
- Through button or web page volume adjustment
- Network time synchronization
- Time Plan (task management)
- Incoming call multicast
- Dynamic multicast function
- HTTP API
- Action URL / Active URI

Call Functions

- Call out / answer / reject
- Call waiting
- Intercom, Multicast
- Speed dial
- Anonymous call (Hide caller ID)

Audio

- Narrowband codec: G.711A/U, G.729A/B, iLBC, G.723, G.726-32K
- Wideband codec: G.722, Opus
- Full-duplex hands-free speakerphone with AEC
- DTMF: In-band, Out-of-Band (RFC2833/ SIP INFO)

Video (Only i16SV-02P)

- Sensor: 1/2.8" color CMOS
- Pixels: 2 Mega
- Video coding: H.264
- Resolution: 720P/1080P
- Minimum illumination: 0.1Lux, support for infrared illumination
- Viewing angle:
 - Diagonal: 126°
 - Horizontal: 98°
 - Vertical: 65°

Network

- Physical: 10/100 Mbps Ethernet
- IP mode: IPv4/IPv6/IPv4&IPv6
- IP configuration: Static IP / DHCP / PPPoE
- VPN: L2TP / OpenVPN
- VLAN
- LLDP
- Qos

Protocols

- SIP2.0 over UDP/TCP/TLS
- RTP/RTCP/SRTP
- STUN
- DHCP
- IPv6
- PPPoE
- L2TP
- OpenVPN
- SNTP
- FTP/TFTP
- HTTP/HTTPS
- TR-069

Deployment & Management

- Auto-provisioning via FTP/TFTP/HTTP/HTTPS/DHCP OPT66/SIP PNP/TR-069
- Web management portal
- Web-based packet dump
- Configuration export / import
- Firmware upgrade
- Syslog

Physical Specifications

- 2 DSS key (support LED)
- RJ45 port x1: connect the network
 - Power over Ethernet (IEEE 802.3af), class 3
- Line out port x1: connect the active speaker
 - Out: adjustable by volume, max up to 1.2Vpp.
 - Port: terminal socket
- Recording output port x1: connect audio device

- Out: mixed output of local microphone voice and call voice recording
- Impedance: 15 Ohm
- Port: terminal socket
- Short circuit input and output port x2 (built-in relay)
 - Relay: MAX DC30V / 2A, AC125V / 0.5A
 - Active switching output: 12V/500mA DC (only 1 relay support)
 - Port: terminal socket
- Tamper alarm switch x1
- TF card slot x1: connect TF card
- DC port x1: DC power input
 - DC power input: DC12V~24V/1A
 - Port: 2 Pin terminal socket
- Protection level: IP65 and IK10
- Housing material: aluminum alloy shell
- Installation: wall-mounted
- Working temperature: -30℃ ~ 60℃
- Storage temperature: -40℃ ~ 70℃
- Working humidity: 10~95%
- Net weight/box: 9.5 kg
- Gross weight/box: 10.05 kg
- Device dimensions: 195x120x40 mm
- Gift box dimensions: 260x165x62 mm
- Outer CTN dimensions: 348x328x280 mm (10 PCS)

The above specifications may be updated in the future without prior notice. All hardware/software/physical features should be based on the final shipped products.

www.fanvil.com

Add: 10F, Block A, Dualshine Global Science Innovation Center, Honglang North 2nd Road, Bao'An District, Shenzhen, China

Tel: +86-755-2640-2199 Fax: +86-755-2640-2618 Email: sales@fanvil.com