

i30 SIP Video Door Phone

The design of i30 SIP Video Door phone is based on experience and knowledge of Fanvil VoIP phone development. Voice transmission uses standard IP / RTP protocol and video transmission adopts RTSP. I30 have a variety of enterprise-level features and it is compatible with lots of major platforms, such as 3CX, Asterisk, Broadsoft, Elastix, etc.

The i30 SIP Video door phone is designed for operation in indoor conditions. The robust mechanical construction offers protective coverage rating against dust and water (IP65).

The i30 is economical devices with triple function(All in one)- Access control by call, code , indoor switch and RFID card

Highlights

- ✓ Small and exquisite, easy to install
- ✓ Graphical Status lights
- ✓ Comfortable keyboard feel, soft backlight
- ✓ All-in-One(Access Control, Intercom and Broadcasting)
- ✓ Compatible with standard SIP(RFC3261) protocol and main IPPBX/IMS platform
- ✓ Access by call, code , indoor switch and RFID card
- ✓ Build-in 3W speaker and AEC, support high quality hand-free communication
- ✓ System online maintenance and management



Access control function

- Two SIP lines, support SIP 2.0 (RFC3261) and related RFC
- Full-duplex handsfree (HF)
- Default Auto Answer
- Open the door operation: DTMF, password, RFID card, switch
- Support 200,000 door open records
- Support 2000 remote access list
- Support 2000 RFID cards
- Support electric lock internal or external power supply options
- Support customized DSS keys
- Network Time Synchronization
- Action URL / Active URI remote control

Audio

- Narrowband speech codec: G.711a / u, G.723.1, G.726-32K, G.729AB
- Broadband speech codec: G.722
- Full Duplex Echo Cancellation (AEC)
- DTMF: In-band, out-of-band DTMF (RFC2833) / SIP Info

Video

- Sensor: 1/4 "color CMOS
- Pixels: 1 million

- Video codec: H.264
- Resolution: The main stream 1280 * 720
Sub-stream 640*360, 352*288, 32*240
- Viewing angle: 110 ° (H), 95 ° (V)
- Minimum illumination: 1Lux, temporarily does not support infrared lighting

Networking/ Protocols

- Support PoE (802.3af)
- Primary and secondary DNS servers are supported
- Support VLAN
- Support SNTP client
- Support VPN L2TP / openVPN
- Support SRTP
- Support HTTP / HTTPS web pages
- Support Qos: 802.1p / q, DSCP
- Support MD5 authentication
- Support Web Filter
- DHCP / static / PPPoE
- Support STUN

Physical Specifications

- 1 DSS button (speed dial button)
- 4 indicator lights (including hot-key backlight)
- Numeric keypad

- 1 indoor switch
- 1 relay: MAX DC30V / 1A, AC125V / 0.5A
- Active switching output: 12V / 700mA DC
- RFID reader: ID (EM4100) standard type
IC(MIFARE ONE) custom type
- RFID card number output: positive sequence output 8H10D
- Microphone: -38dB
- Speaker: 4Ω / 3W
- WAN port: RJ-45, 10 / 100M adaptive
- Power supply: 12V ± 15% / 1A DC or POE
- PoE: 802.3af (Class 3 - 6.49 to 12.95W)
- Standby power: 2.76W, 12V / 230mA
- Network cable: CAT5 or better
- Shell material: metal surface, ABS bottom shell
- Installation: wall-mounted installation
- Operating temperature: -20 ~ 60 °C
- Storage temperature: -40 ~ 70 °C
- Relative humidity: 10 ~ 90%
- Protection class: IP65
- Equipment size: 160x93x35mm
- Packing size: 178x104x55mm
- Equipment weight: 330g
- Package weight: 450g